



Data360[®] Analyze

Installing and configuring R



Table of contents

1. Installing and configuring R	1
1.1 Installing and configuring R in Windows	1
1.2 Installing and configuring R in Linux	3
2. Contact us	7

1. Installing and configuring R



Note: R and the RServe client are not distributed by Infogix. The R node communicates with these programs to execute R scripts.

Disclaimer

Open-source R is available under separate open source software license terms and is not part of Data360 Analyze. As such, open-source R is not within the scope of your license for . Open-source R is not supported, maintained, or warranted in any way by Infogix. Download and use of open-source R is solely at your own discretion and subject to the free open source license terms applicable to open-source R.

1.1 Installing and configuring R in Windows

The following steps are appropriate for the majority of Windows installations, and assume that the server and R are on the same Windows machine. If extensive resources will be needed to process data using R scripts, R can be located on a separate server, if this is the case, please skip to [step 4](#).



Caution: If R is to be deployed on the same machine as it is important to ensure sufficient system resources (especially RAM) are available to handle the peak processing load.

1. Install R as per the instructions on <https://www.r-project.org/>

The current version of the R node was tested against R 3.3.2-3.el7.x86_64.

2. Start R by using the Start menu created by the R installer.

An R window opens.

3. Install the additional packages required for the R node to execute by running the following commands inside your R window:

- `install.packages("Rserve")`
- `install.packages("jpeg")`
- `install.packages("png")`

The current version of the R node was tested against the following package versions (later versions of these libraries may not be compatible with the R node):

- Rserve 1.7-3
- png 0.1-7
- jpeg 0.1-8

4. Install the Rserve client into your existing server, as follows:

- Navigate to Rserve's website (currently <http://rforge.net/Rserve/>) and download the Rserve_1.8-0.zip binary.



Note: Later versions of Rserve may not be compatible with the R node.

- Unzip the downloaded file, then navigate to Rserve/java. Copy the REngine.jar and Rserve.jar files.
- If you are using the server edition, paste the **REngine.jar** and **Rserve.jar** files into the following location: `<Data360Analyze site directory>/lib/java`
If you are using the desktop edition, paste the **REngine.jar** and **Rserve.jar** files into the following location:

`%LOCALAPPDATA%/Data360Analyze/site/lib/java` if you selected **Local User** during installation or `C:/ProgramData/Data360Analyze/site/lib/java` if you selected **All Users** during installation.

5. Download the R Node Pack from the Zendesk [downloads](#) web page.

Open and import the R node LNA. See the integrated product help for more information on importing library nodes.

6. By default, the R node is imported into your **My Documents** folder.

If you are using the server edition, you can make the R node available for all users on the server by moving it to the **Public Documents** folder. To do this, from the Directory, click **My Documents**, then select the R node. Click the menu button in the details panel and select **Move to Public Documents**.



Caution: Prior to running the R node, you first need to [start the Rserve server](#). The Rserve server needs to be started whenever the machine on which it is running is rebooted.

Starting Rserve server

1. If you do not have an R window open, start R, using the Start menu icon created by the R installer.
2. Run the following commands in the R window:
 - `library(Rserve)`
 - `Rserve()`

You have now started the Rserve server. You can close the R window and the Rserve server will continue to run normally.



Note: There is no Startup menu item to shut down the Rserve server. To close Rserve, open Windows **Task Manager** and end the process named `Rserve.exe`.

Once you have completed the above steps, see the R node topic in the integrated product help for information on running the R node.

1.2 Installing and configuring R in Linux

The following steps assume that the Server and R are on two separate machines. However, it is also possible to install them on the same machine.



Caution: If R is to be deployed on the same machine as it is important to ensure sufficient system resources (especially RAM) are available to handle the peak processing load.

1. Install R as per the instructions on <https://www.r-project.org/>

The current version of the R node was tested against R 3.3.2-3.el7.x86_64.

If you choose to compile R from source, configure it with the following options to ensure that the supporting binaries for the R node are available:

- `--enable-R-shlib`
- `--with-libpng`
- `--with-jpeglib`

2. Start R by navigating to the R installation `bin` directory and executing the **R** program.

An R prompt opens, allowing you to enter R commands.

3. Install the additional packages that the R node needs to execute by typing the following commands in the R prompt window:

- `install.packages("Rserve")`
- `install.packages("jpeg")`
- `install.packages("png")`

The current version of the R node was tested against the following package versions (later versions of these libraries may not be compatible with the R node):

- Rserve 1.7-3
- png 0.1-7
- jpeg 0.1-8




Note: As CRAN packages for Linux are typically distributed as source packages, the Linux server must be provisioned with system libraries that permit the compilation of the prerequisite CRAN packages, e.g. gcc with the libraries for Fortran compilation.


4. Exit R by typing the command `q()`.

5. Start the X server on your machine, and ensure the identity that runs R has access to X. For most systems, this will mean running `xinit` as root and then ensuring that the `DISPLAY` environment variable is set to `:0` for the identity that starts Rserve. The identity that starts Rserve does not need to be in a graphical environment.
6. Confirm the location of the R temporary directory. The R node will use this directory to store image files as they are in transit from the R server to the server. While the size of each image should be relatively small, they can add up over time, especially on systems with lots of users. The temporary directory can be set up via the standard R mechanisms (see R's `tempdir()` help for more information).
7. Configure Rserve as per the Rserve instructions at: <http://rforge.net/Rserve/doc.html#conf>. This is a three-step process:
 - Create a custom `Rserv.conf` configuration file.
 - Consider the security issues discussed in the section that begins "A note about security". The recommended security steps are important to help prevent unauthorized users from executing arbitrary R code on your R Server.
 - Ensure that the following options are in your `Rserv.conf` file:
 - `encoding utf8`
 - `interactive no`
 - `remote enable`
8. Navigate to the R bin directory and start the Rserve server by running the following command, where `<Rserv.conf>` is a reference to your custom `<Rserv.conf>` file:

```
R CMD Rserve --RS-conf <Rserv.conf>
```
9. Install the Rserve client on the Server as per the following steps:
 - a. Download the `Rserve_1.8-3.tar.gz` file from the Rserve website: <http://rforge.net/Rserve/>.

 **Note:** Later versions of Rserve may not be compatible with the R node.

 - b. Unzip and untar the downloaded file, then navigate to: `Rserve/inst/java`.
 - c. Add the **REngine.jar** and **Rserve.jar** files to the following location:
`<Data360Analyze site directory>/lib/java`
10. Download the R Node Pack from the Zendesk [downloads](#) web page.



Open and import the R node LNA. See the integrated product help for more information on importing library nodes.

11. By default, the R node is imported into your **My Documents** folder.

If you are using the server edition, you can make the R node available for all users on the server by moving it to the **Public Documents** folder. From the Directory, click **My Documents**, then select the R node. Click the menu button in the details panel and select **Move to Public Documents**.

12. If you configured R to require authentication, ensure that your R node users are given their connection information to enable them to sign in. If the and R Servers are on different machines, you should provide users with a hostname, and a port if you used a custom port for Rserve.

Once you have completed the above steps, see the R node topic in the integrated product help for information on running the R node.


2. Contact us

If you encounter any technical issues, we recommend that you visit the support portal at support.infogix.com.

If your query has not been discussed previously, you can create a new topic and receive answers from our product experts.

Alternatively, you can log a support ticket:

1. Select **Sign in** from the top right corner of the screen.
2. If you have already registered, enter your **Email** and **Password**, then click the **Sign in** button.
Or, if you are not a registered support portal user, click **Sign up**:



Sign in to Infogix

Email

Password

☐ Stay signed in

Sign in

[I am an Agent](#)

[Forgot my password](#)

[New to Infogix? Sign up](#)

Have you emailed us? [Get a password](#)

If you've communicated with our support staff through email previously, you're already registered. You probably don't have a password yet, though.

3. Once you have registered and signed in, select **Submit a request** from the top right corner of the screen.
4. Complete all fields, then click **Submit** at the bottom of the screen.

Download

Infogix recommends that you use the latest version of the product. To download Data360 Analyze, please go to <https://www.infogix.com/data3sixty/analyze/analyze-download/>.

Our product is constantly evolving and input from you is highly valued. If you have any suggestions, please contact the product team by submitting a feature request on the [Community](#).

Copyright

© Copyright 2020 Infogix, Inc. All rights reserved.

Confidential—Limited distribution to authorized persons only, pursuant to the terms of Infogix, Inc. license agreement. This document is protected as an unpublished work and constitutes a trade secret of Infogix, Inc.

Apache Hive, Hive are trademarks of The Apache Software Foundation.

Apache Spark, Spark, Apache, and the Spark logo are trademarks of The Apache Software Foundation.

Microsoft and SharePoint are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

MongoDB and Mongo are registered trademarks of MongoDB, Inc.

Qlik®, Qlik Tech®, QlikView® and the Qlik Tech logos are trademarks or registered trademarks of Qlik Tech International AB.

Salesforce, SALESFORCE.COM and others are trademarks of salesforce.com, inc. and are used here with permission.

Tableau and Tableau logo are registered trademarks of Tableau Software, Inc.

TIBCO® Enterprise Runtime for R are either registered trademarks or trademarks of TIBCO Software Inc. and/or its subsidiaries in the United States and/or other countries.

This document and the information contained herein are the property of Infogix, Inc. Reproduction or use in whole or in part of this document and the information contained herein by anyone without prior written consent of Infogix, Inc. is prohibited.

Disclaimer

Infogix, the Infogix logo, ACR, ACR/Detail, ACR/Summary, ACR/Workbench, ACR/Connector, Infogix Assure, Infogix Insight, ACR/Instream, ACR/File, Infogix ER, Infogix Perceive, Data3Sixty, and Data360 are registered trademarks of Infogix, Inc. Data3Sixty Analyze, Data3Sixty Govern, Data3Sixty DQ+, Data360 Analyze, Data360 Govern and Data360 DQ+ are trademarks of Infogix, Inc. Any other trademarks or registered trademarks are the property of their respective owners.



Note: The images in this document are used purely for illustrative purposes and may display license-dependent functionality.

Document ID: AYZ-R-9

Date of issue: Monday, January 13, 2020